



Date: 22.07.2011  
Date of test: 22.07.2011  
GOV-0807

**CUSTOMER** ..... :  
MULTIFARB SP Z.O.O.  
UL.HANDLOWA 4  
35-103 RZESZÓW  
POLONIA  
**PRODUCT** ..... : **RHXZ-7950**  
**DESCRIPTION...** : HYBRID METALLIC TEXTURE  
**COLOUR** ..... : GREY  
**RAL** ..... :  
**BATCH** ..... : 84553  
**TOXICITY** ..... : S0  
**C.SCHED** ..... :  
**Nr. LICENCE** .. :

**TEST**

=====

**SPECIFICATIONS**

=====

**RESULTS**

=====

\*\*\* POWDER PROPERTIES \*\*\*

Thickness	UNE 48031-80	50 - 70 µm	60 µm
Curing	190 °C	15 min	15 min
Application System			Triboelétric / Electrostátic
Application Properties			Good

\*\*\* FILM PROPERTIES \*\*\*

Aspect			GOOD
Gloss 60°	UNE EN ISO 2813	3 - 8 %	8 %
Mandrel Folding	UNE EN ISO 1519	< = 5 mm	5 mm
Direct Impact	UNE-EN ISO 6272	> = 60 cm	60 cm
Inverse Impact	UNE-EN ISO 6272	> = 50 cm	50 cm
Adhesion	UNE EN ISO 2409		GTO

